

Funnels for many purposes

Funnels in alu

The Geovent Extraction Funnels are available in the following dimensions: 80, 100 and 125 mm. The Funnels may be connected to a Coupling, ensuring high mobility for the operator, where conventional extraction arms cannot be used. The Funnels are executed in aluminium/steel and are powder enamelled (RAL 1007). Available with/without damper and magnet.

Funnels with magnet ensure the operator a high degree of freedom, since it may be attached to both horizontal and vertical magnetic surfaces, close to the source of pollution (see photograph below). The Alu-Funnel may be mounted on one of the Geovent ASA-Arms.



Alu funnel with magnet

Area of application	Model	(m ³ /h)	Art. no.				All measurements in mm		
			Funnel	w/damper	w/magn	w/magn and damper	A	B	C
Weldingfunnes	Welding								
Oil mist	80	300-400	06-121	+ 12-005	06-014	06-015	205	245	80
Soldering	100	400-600	06-122	+ 12-006	06-020	06-021	220	245	100
Funnes	125	600-800	06-123	+ 12-012	06-025	06-026	250	250	125
Wapours	Minifunnel								
Grinders	80	300-400	06-095	+ 12-005	06-051	06-052	58 x 132	247	80
Lathes Etc.	100	400-600	06-096	+ 12-006	06-053	06-054	76 x 153	227	100