

ALUMINIUM SYSTEM 50 + 75 + 100

PP – CHEMICAL RESISTANT SYSTEM 63 + 75 + 100

FLEX SYSTEM 50 AL & AS

AIRFLOW ALARM SYSTEM 10



AIR VOLUME AND REACH

SYSTEM 50

Air volume: 45-85 m³/h
Max. reach: 1660 mm

SYSTEM 75

Air volume: 80-180 m³/h
Max reach: 1990 mm

SYSTEM 100

Air volume: 140-400 m³/h
Max reach: 2630 mm



AIR VOLUME AND REACH

SYSTEM 63

Air volume: 60-120 m³/h
Max reach: 1550 mm

SYSTEM 75

Air volume: 80-180 m³/h
Max reach: 1990 mm

SYSTEM 100

Air volume: 140-400 m³/h
Max reach: 2630 mm



AIR VOLUME AND REACH

FLEX – SYSTEM 50

Air volume: 45-85 m³/h
Max. reach: 900 mm


STANDARDS

SYSTEM 50 FLEX

ESD: IEC 61340-5-1:2016



Airflow < 4 m/sek:



ANTISTATIC ESD/EX SYSTEM 50 + 75 + 100

WORK CABINETS SYSTEM 25



STANDARDS ESD & EX	
SYSTEM 50	SYSTEM 75 & SYSTEM 100
ESD: IEC 61340-5-1:2016	ESD IEC 61340-5-1:2016
	EX: EN 80079-36:2016 EN 80079-37:2016



AIR VOLUME & SIZE
SYSTEM 25
Air volume: 117-850 m³/h

L x B [mm]:
Type 1: 1000 x 600
Type 2: 635 x 480
Type 3: 420 x 320

