

Extraction arm

PERMA arm

Geovent A/S offers a new extraction arm, the PERMA, in our program of extraction arms.

The PERMA arm is suitable for use at hairdressers, dental clinics, jewelers, pharmacies, veterinarians, podiatrists, schools, laboratories / hospitals & food manufacturing industries. In addition, the suction arm is suitable for the electronics industry (ESD approved), as well as for the chemicals, plastics and engineering industries.

The PERMA arm consists of a standard Aluminium tube with two molded plastic (POM) joints. Available in two pipe sizes $\varnothing 57$ and $\varnothing 76$. As standard with anodized surface. Equipped with removable black plastic covers for easy cleaning.

The flexible, self-supporting construction consists of 2 or 3 parts Aluminium tubes, bracket for mounting and a large selection of accessories. The key element of the program is the patented suspension system for spiral pipe and the cleaning friendly arm joints. The joint can increase efficiency by approximately 25% compared to comparable arms on the market.

The system is even flexible and easy to install.

Extraction arms is suitable for use in environments with no special demands for chemical resistance or conductive characteristics. Point extraction arms is offered in white or black joints.

The antistatic extraction arms type $\varnothing 57$ -76 ESD is suitable for use in ESD areas. This means that for example. Electronics industry can use these extractor arms without danger of static electricity associated with extraction processes. ESD is available only in black.

General:

$\varnothing 57$ mm 50-90m³/h
 $\varnothing 76$ mm 80-180m³/h



Available in black or white joints



PERMA arm ø57 mm

| Art. No | Description type ø57 |
|-----------|--------------------------------|
| 10-300H/S | 380 mm 2 joint white or black |
| 10-301H/S | 480 mm 2 joint white or black |
| 10-302H/S | 580 mm 2 joint white or black |
| 10-303H/S | 750 mm 3 joint white or black |
| 10-304H/S | 950 mm 3 joint white or black |
| 10-305H/S | 1150 mm 3 joint white or black |
| 10-306H/S | 1250 mm 3 joint white or black |
| 10-307H/S | 1350 mm 3 joint white or black |
| 10-308H/S | 1420 mm 3 joint white or black |
| 10-309H/S | 1490 mm 3 joint white or black |

All PERMA arms are incl. damper

PERMA arm ø76 mm

| Art. No. | Description type ø76 |
|-----------|--------------------------------|
| 10-400H/S | 380 mm 2 joint white or black |
| 10-401H/S | 480 mm 2 joint white or black |
| 10-402H/S | 580 mm 2 joint white or black |
| 10-403H/S | 750 mm 3 joint white or black |
| 10-404H/S | 950 mm 3 joint white or black |
| 10-405H/S | 1150 mm 3 joint white or black |
| 10-406H/S | 1250 mm 3 joint white or black |
| 10-407H/S | 1350 mm 3 joint white or black |
| 10-408H/S | 1420 mm 3 joint white or black |
| 10-409H/S | 1490 mm 3 joint white or black |

All PERMA arms are incl. damper

PERMA arm ø57 mm, ESD

| Art. No. | Description type ø57 ESD |
|----------|-------------------------------|
| 10-350 | 380 mm 2 joint only in black |
| 10-351 | 480 mm 2 joint only in black |
| 10-352 | 580 mm 2 joint only in black |
| 10-353 | 750 mm 3 joint only in black |
| 10-354 | 950 mm 3 joint only in black |
| 10-355 | 1150 mm 3 joint only in black |
| 10-356 | 1250 mm 3 joint only in black |
| 10-357 | 1350 mm 3 joint only in black |
| 10-358 | 1420 mm 3 joint only in black |
| 10-359 | 1490 mm 3 joint only in black |


All PERMA arms are incl. damper

PERMA arm ø76 mm, ESD

| Art. No. | Description type ø76 ESD |
|----------|-------------------------------|
| 10-450 | 380 mm 2 joint only in black |
| 10-451 | 480 mm 2 joint only in black |
| 10-452 | 580 mm 2 joint only in black |
| 10-453 | 750 mm 3 joint only in black |
| 10-454 | 950 mm 3 joint only in black |
| 10-455 | 1150 mm 3 joint only in black |
| 10-456 | 1250 mm 3 joint only in black |
| 10-457 | 1350 mm 3 joint only in black |
| 10-458 | 1420 mm 3 joint only in black |
| 10-459 | 1490 mm 3 joint only in black |

All PERMA arms are incl. damper

Dimensions




Mounting bracket / base

The extraction arms in $\varnothing 57$ mm and $\varnothing 76$ mm is offered for either ceiling mounting or wall mounting. Can be mounted in, rounded tube or white painted socket pipe. The extraction arms in the two types of pipes are all available as table mounting with special crafted table bracket, either on the edge of the table which can be removable or can be made a permanent settlement on the table.



Mounting bracket / pipe



| Art. No. | Description |
|----------|--|
| 10-315 | Base for wall/ceiling type $\varnothing 57$ 180 mm |
| 10-415 | Base for wall/ceiling type $\varnothing 76$ 180 mm |

| | |
|---------|--|
| 10-500 | PERMA $\varnothing 57$ Table bracket mounted in $\varnothing 105$ mm hole in the table, connection $\varnothing 80$ mm |
| 10-500A | PERMA $\varnothing 76$ Table bracket mounted in $\varnothing 105$ mm hole in the table, connection $\varnothing 80$ mm |
| 10-501 | PERMA $\varnothing 57$ Table bracket mounted on the edge of table |
| 10-501A | PERMA $\varnothing 76$ Table bracket mounted on the edge of table |

| | |
|--------|--|
| 10-365 | Base for wall/ceiling type $\varnothing 57$ ESD 180 mm |
| 10-465 | Base for wall/ceiling type $\varnothing 76$ ESD 180 mm |

| | |
|---------|---|
| 10-365B | ESD Table bracket, installed in $\varnothing 105$ mm hole in the table, $\varnothing 57$ mm, connection $\varnothing 80$ mm |
| 10-465B | ESD Table bracket, mounted in $\varnothing 105$ mm hole in the table, $\varnothing 76$ mm, connection $\varnothing 80$ mm |
| 10-365C | ESD Table bracket, installed on edge of table, $\varnothing 57$ mm, connection $\varnothing 80$ mm |
| 10-465C | ESD Table bracket, mounted on edge of table, $\varnothing 76$ mm, connection $\varnothing 80$ mm |

| Art. No. | Description |
|----------|--|
| 10-502 | Socket pipe $\varnothing 100$ with side pipe 250 mm |
| 10-503 | Socket pipe $\varnothing 100$ with side pipe 350 mm |
| 10-504 | Socket pipe $\varnothing 100$ with side pipe 500 mm |
| 10-505 | Socket pipe $\varnothing 100$ with side pipe 750 mm |
| 10-506 | Socket pipe $\varnothing 100$ with side pipe 1000 mm |

| Art. No. | Description |
|----------|---|
| 10-507 | Smooth pipe 500 mm |
| 10-508 | Smooth pipe 1000 mm |
| 10-509 | Wall mount |
| 10-510 | Ceiling mount closet $\varnothing 100$ mm |
| 10-511 | Ceiling mount through-going $\varnothing 100$ mm |
| 10-512 | Branch pipe $\varnothing 100$ mm, 620x250 mm - used by 2 outlet for 2 arm |
| 10-514 | Support bracket for ceiling pipes |

Accessories

Geovent offer a great range of accessories for suction arms: hoppers, suction pens and hoods with and without flexible tube/hose. There are different accessories for each type of extraction arms $\varnothing 57$, $\varnothing 57$ ESD, $\varnothing 76$ and $\varnothing 76$ ESD.

The suction nozzles are available in clear, impact resistant polycarbonate with an orifice diameter of up to 380 mm, or aluminium which can withstand considerable heat. Usually with rotary damper to open and close the air passage. The flexible pipe section allows replacement of the suction port / screen, while acting as a pivot.

Round hood



Conical hood



Flat hood



| Type | Art. no. | Description |
|------------------|----------|--|
| $\varnothing 57$ | 10-316 | Round hood $\varnothing 380$ mm |
| $\varnothing 76$ | 10-416 | Hood for industry $\varnothing 380$ mm |

Connection pipe 180 mm included all hoods

| Type | Art. no. | Description |
|----------------------|----------|---|
| $\varnothing 57$ | 10-317 | Conical hood $\varnothing 250$ mm |
| $\varnothing 57$ | 10-318 | Conical hood $\varnothing 250$ mm w. flex pipe 300 mm |
| $\varnothing 57$ | 10-319 | Conical hood $\varnothing 250$ mm |
| $\varnothing 57$ | 10-320 | Conical hood $\varnothing 250$ mm w. flex pipe 300 mm |
| $\varnothing 57$ | 10-327 | Conical hood $\varnothing 120$ mm w. adjustable hose 400 mm |
| $\varnothing 57$ | 10-329 | Conical hood oval 140x180 mm |
| $\varnothing 57$ ESD | 10-372 | Conical hood $\varnothing 150$ mm w. adjustable hose 400 mm |
| $\varnothing 76$ | 10-417 | Conical hood $\varnothing 250$ mm |
| $\varnothing 76$ | 10-418 | Conical hood $\varnothing 250$ mm w. flex pipe 300 mm |
| $\varnothing 76$ | 10-419 | Conical hood $\varnothing 250$ mm |
| $\varnothing 76$ | 10-420 | Conical hood $\varnothing 250$ mm w. flex pipe 300 mm |

Connection pipe 180 mm included all hoods

| Type | Art. no. | Description |
|------------------|----------|----------------------|
| $\varnothing 57$ | 10-323 | Flat hood 340x250 mm |
| $\varnothing 76$ | 10-425 | Flat hood 340x250 mm |

Connection pipe 180 mm included all hoods

Aluminium hood



Extraction pen



Extraction pen w/hose



| Type | Art no. | Description |
|---------|---------|--------------------------------|
| ø57 | 10-321 | Aluminium hood conical ø150 mm |
| ø57 ESD | 10-366 | Aluminium hood conical ø150 mm |
| ø76 | 10-421 | Aluminium hood conical ø150 mm |
| ø76 ESD | 10-466 | Aluminium hood conical ø150 mm |

Connection pipe 180 mm included all hoods

The suction pen is offered to both dimensions. Comes complete with couplings, rotary dampers and flexible tube, and can be completely customized as you wish.

| Type | Art no. | Description |
|---------|---------|--|
| ø57 | 10-324 | Suction pen 250 mm |
| ø57 | 10-324A | Suction pen press flange ø57 mm, 250 mm |
| ø57 | 10-325 | Suction pen 350 mm |
| ø57 | 10-325A | Suction pen press flange ø57 mm, 350 mm |
| ø57 ESD | 10-367 | Suction pen 250 mm |
| ø57ESD | 10-367A | Suction pen press flange with flextube ø57 mm, 150 mm |
| ø57 ESD | 10-368 | Suction pen 350 mm |
| ø76 | 10-422 | Suction pen 250 mm |
| ø76 | 10-423 | Suction pen 350 mm |
| ø76 ESD | 10-467 | Suction pen 250 mm |
| ø76 ESD | 10-467A | Suction pen press flange ø76 mm, L 250 mm, ESD |
| ø76 ESD | 10-468 | Suction pen 350 mm |
| ø76 ESD | 10-468A | Suction pen press flange ø76 mm, L 350 mm, ESD |
| ø57 | 10-326 | Suction pen 150 mm w. flex pipe 300 mm |
| ø57 | 10-326A | Suction pen press flange with flextube ø57 mm, 150 mm |
| ø57 ESD | 10-369 | Suction pen ø150 mm w. flex pipe 300 mm |
| ø57 ESD | 10-369A | Suction pen press flange ø 57 mm, 150 mm with flextube 300 mm, ESD |
| ø57 ESD | 10-370 | Suction pen ø150 mm w. flex pipe 600 mm 1 led m. spjæld |
| ø57 ESD | 10-371 | Suction pen ø150 mm w. flex pipe 600 mm m. spjæld |
| ø76 | 10-424 | Suction pen 150 mm w. flex pipe 300 mm |
| ø76 ESD | 10-469 | Suge Suction pen spids 150 mm w. flex pipe 300 mm |
| ø76 ESD | 10-469A | Suction pen press flange ø76 mm, L 150 mm, ESD |

Connection pipe 180 mm included all hoods

The different arms can regardless of the pipe thickness, be fitted with a flexible tube, which makes the suction funnel and suction pen easy to fix in a variety of postures. Flex pipe can be used by all mounting types ceiling, wall and table mounting.

Guide for PERMA arm use:

| Sectors | PERMA arm | | | |
|--|----------------|------------------|------------------|------------------|
| | ø57 | ø57 ESD | ø76 | ø76 ESD |
| Dental Technician | x ¹ | | x ¹ | |
| Veterinarians and clinics | | | x ² | |
| Podiatrists | x ⁶ | | | |
| Nail Clinic | x ¹ | | | |
| Doctors and specialists | x ¹ | | x ⁵ | |
| Laboratories | | x ^{1 2} | x ^{1 2} | x ^{1 2} |
| Hospitals | | | x ¹ | |
| Pharmacies | | | x ² | |
| Gold and silversmiths | x ¹ | | x ² | |
| Hairdressing | x ³ | | | |
| Classrooms in schools, colleges and universities | x ¹ | | x ^{1 4} | |
| Electronics industry | | x ¹ | | x ¹ |

- Chemicals: ¹ Extraction arm with flexible hoses and suction tip
 ² Extraction arm with dome or funnel
 ³ Extraction arm with flat screen, dome or funnel
- Odour: ² Extraction arm with dome or funnel
- Gas, smell: ⁴ Extraction arm with suction funnel or dome
- Solder Fume: ¹ Extraction arm with flexible hoses and suction tip
- Anaesthetic Gases: ⁵ Extraction arm with suction funnel
- Dust: ¹ Extraction arm with flexible hoses and suction tip
- Grinding dust: ⁶ Extraction arm with suction funnel and hose (Item no.10-327)

