





- Duct fan with circular connections.
- Proven performance and reliability.
- Compact with high capacity and efficiency.
- Low sound levels.
- Operational in both 50 and 60 Hz.
- Impeller with backward curved blades.
- The external rotor motor has maintenance-free sealed ball-bearings and is very energy efficient.
- For speed control a transformer or electronic speed controller can be connected.
- Integrated motor protection.
- Junction box has enclosure class IP 54.
- Fan housing is manufactured from galvanized sheet steel.
- The fan is intended to be installed in a duct system.
- A duct connected fan can be installed outside or in damp environments.
- Easy installation in any position.
- To comply with the ErP 2018 regulation, a local demand controller must be used.


PRESSURE/FLOW



POWER/FLOW



SFP



TECHNICAL DATA

Voltage	230 V
Frequency	50 Hz (60 Hz)
Phase	1 ~
Current	0,26 A
Power	60 W
Speed	2530 r.p.m.
Max. temp of transported air	80 °C
Sound pressure level, 3 m	38 dB(A)
Weight	2,6 kg
Enclosure class	44 IP
Wiring diagram	4040001

ACCESSORIES

- Mounting bracket Kit MB
- Mounting clamp MK 125
- Safety grille BSV 125
- Back draught shutter RSK 125
- Louvre YG 125
- Louvre shutter VK 125
- Filterbox FLK 125
- Filterbox FLF 125
- Silencer LDC 125
- Transformer controller VRTE C
- Transformer controller VRDE 1.5
- Speed controller VRS 0.5
- Local Demand Controller Kit

SOUND DATA

	L_{WA} tot dB (A)	63	125	250	500	1K	2K	4K	8K
Surrounding 230 V	45	18	28	38	38	40	33	35	30
Outlet 230 V	70	50	62	66	63	62	60	56	49
Inlet 230 V	70	48	62	65	65	63	60	56	50
Inlet 165 V	67	46	60	63	61	59	56	52	45
Inlet 135 V	63	44	57	58	57	54	50	45	36
Inlet 110 V	56	39	51	51	50	47	42	36	25
Inlet 80 V	46	30	43	41	37	32	23	23	17

MORE INFORMATION



Find out the latest updated information about this product by visiting www.ostberg.com or scanning this QR code.

DIMENSIONS (mm)

